

# 034 FOCUS OSPA ANTIFOAM

## Dolphin Pacific

Chemwatch Hazard Alert Code: 1

Chemwatch: 5537-87

Issue Date: 23/08/2023

Version No: 2.1

Print Date: 02/05/2024

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

S.GHS.NZL.EN.E

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### Product Identifier

|                               |                         |
|-------------------------------|-------------------------|
| Product name                  | 034 FOCUS OSPA ANTIFOAM |
| Chemical Name                 | Not Applicable          |
| Synonyms                      | Not Available           |
| Chemical formula              | Not Applicable          |
| Other means of identification | Not Available           |

#### Relevant identified uses of the substance or mixture and uses advised against

|                          |   |
|--------------------------|---|
| Relevant identified uses | Antifoam concentrate : Dilution rates: 1ml-5mls per 1000litres. |
|--------------------------|---|

#### Details of the manufacturer or supplier of the safety data sheet

|                         |   |
|-------------------------|---|
| Registered company name | Dolphin Pacific   |
| Address                 | 1 Saunders Place Auckland 1026 New Zealand                              |
| Telephone               | 0800 365 722  |
| Fax                     | Not Available   |
| Website                 | <a href="http://dolphinpacific.co.nz/">http://dolphinpacific.co.nz/</a> |
| Email                   | sales@dolphinpacific.co.nz  |

#### Emergency telephone number

|                                   |                                     |
|-----------------------------------|-------------------------------------|
| Association / Organisation        | CHEMWATCH EMERGENCY RESPONSE (24/7) |
| Emergency telephone numbers       | +64 800 700 112                     |
| Other emergency telephone numbers | +61 3 9573 3188                     |

Once connected and if the message is not in your preferred language then please dial 01

### SECTION 2 Hazards identification

#### Classification of the substance or mixture

|   |                |
|---|----------------|
| Classification <sup>[1]</sup>                   | Not Applicable |
| Determined by Chemwatch using GHS/HSNO criteria | Not Available  |

#### Label elements

|                     |                |
|---------------------|----------------|
| Hazard pictogram(s) | Not Applicable |
| Signal word         | Not Applicable |

#### Hazard statement(s)

Not Applicable

#### Precautionary statement(s) Prevention

Not Applicable

#### Precautionary statement(s) Response

Not Applicable

#### Precautionary statement(s) Storage

Not Applicable

#### Precautionary statement(s) Disposal

Not Applicable

### SECTION 3 Composition / information on ingredients

#### Substances

See section below for composition of Mixtures

#### Mixtures

| CAS No        | %[weight] | Name                                       |
|---------------|-----------|--|
| Not Available | 100       | Ingredients determined not to be hazardous |

**Legend:** 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; \* EU IOELVs available

### SECTION 4 First aid measures

#### Description of first aid measures

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with water.</li> <li>▶ If irritation continues, seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul> |
| <b>Skin Contact</b> | <p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>   |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul>  |
| <b>Ingestion</b>    | <ul style="list-style-type: none"> <li>▶ Immediately give a glass of water.</li> <li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>  |

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5 Firefighting measures

#### Extinguishing media

- ▶ Water spray or fog.
- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

#### Special hazards arising from the substrate or mixture

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

#### Advice for firefighters

|                              |  |
|------------------------------|--|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>▶ Avoid spraying water onto liquid pools.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> </ul> |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ Combustible.</li> <li>▶ Slight fire hazard when exposed to heat or flame.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> </ul>  |

Continued...

- ▶ May emit acrid smoke.
  - ▶ Mists containing combustible materials may be explosive.
- Combustion products include:  
carbon dioxide (CO<sub>2</sub>)  
other pyrolysis products typical of burning organic material.

## SECTION 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

|                     |   |
|---------------------|---|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>▶ Wipe up.</li> <li>▶ Place in a suitable, labelled container for waste disposal.</li> </ul>  |
| <b>Major Spills</b> | <p>Moderate hazard.</p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Absorb remaining product with sand, earth or vermiculite.</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### Precautions for safe handling

|                          |  |
|--------------------------|--|
| <b>Safe handling</b>     | <ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ Avoid smoking, naked lights or ignition sources.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ When handling, <b>DO NOT eat, drink or smoke.</b></li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.</li> </ul> |
| <b>Other information</b> | <ul style="list-style-type: none"> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Store in a cool, dry, well-ventilated area.</li> <li>▶ Store away from incompatible materials and foodstuff containers.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>   |

### Conditions for safe storage, including any incompatibilities

|                                |  |
|--------------------------------|--|
| <b>Suitable container</b>      | <ul style="list-style-type: none"> <li>▶ Metal can or drum</li> <li>▶ Packaging as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul> |
| <b>Storage incompatibility</b> | Avoid contamination of water, foodstuffs, feed or seed.  |

Continued...

034 FOCUS OSPA ANTIFOAM

▶ Avoid reaction with oxidising agents

**SECTION 8 Exposure controls / personal protection**

**Control parameters**

**Occupational Exposure Limits (OEL)**

**INGREDIENT DATA**


Not Available

**Emergency Limits**

| Ingredient              | TEEL-1        | TEEL-2        | TEEL-3        |
|-------------------------|---------------|---------------|---------------|
| 034 FOCUS OSPA ANTIFOAM | Not Available | Not Available | Not Available |

| Ingredient              | Original IDLH | Revised IDLH  |
|-------------------------|---------------|---------------|
| 034 FOCUS OSPA ANTIFOAM | Not Available | Not Available |

**Exposure controls**

| <b>Appropriate engineering controls</b>   | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>General exhaust is adequate under normal operating conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> |                      |                        |   |   |   |   |  |                                  |  |   |                                    |
|---|---|----------------------|------------------------|---|---|---|---|--|----------------------------------|--|---|------------------------------------|
|   | <table border="1"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air)</td> <td>0.25-0.5 m/s (50-100 f/min)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s (100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min)</td> </tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).</td> <td>2.5-10 m/s (500-2000 f/min.)</td> </tr> </tbody> </table>  | Type of Contaminant: | Air Speed:             | solvent, vapours, degreasing etc., evaporating from tank (in still air) | 0.25-0.5 m/s (50-100 f/min)                           | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)                                | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min)        | grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion). | 2.5-10 m/s (500-2000 f/min.)              |                                    |
| Type of Contaminant:  | Air Speed:  |                      |                        |   |   |   |   |  |                                  |  |   |                                    |
| solvent, vapours, degreasing etc., evaporating from tank (in still air)   | 0.25-0.5 m/s (50-100 f/min)   |                      |                        |   |   |   |   |  |                                  |  |   |                                    |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)  |                      |                        |   |   |   |   |  |                                  |  |   |                                    |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s (200-500 f/min)   |                      |                        |   |   |   |   |  |                                  |  |   |                                    |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion).  | 2.5-10 m/s (500-2000 f/min.)  |                      |                        |   |   |   |   |  |                                  |  |   |                                    |
|   | <p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood - local control only</td> </tr> </tbody> </table>  |                      | Lower end of the range | Upper end of the range  | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents   | 2: Contaminants of low toxicity or of nuisance value only | 2: Contaminants of high toxicity   | 3: Intermittent, low production. | 3: High production, heavy use  | 4: Large hood or large air mass in motion | 4: Small hood - local control only |
| Lower end of the range  | Upper end of the range  |                      |                        |   |   |   |   |  |                                  |  |   |                                    |
| 1: Room air currents minimal or favourable to capture   | 1: Disturbing room air currents   |                      |                        |   |   |   |   |  |                                  |  |   |                                    |
| 2: Contaminants of low toxicity or of nuisance value only   | 2: Contaminants of high toxicity  |                      |                        |   |   |   |   |  |                                  |  |   |                                    |
| 3: Intermittent, low production.  | 3: High production, heavy use   |                      |                        |   |   |   |   |  |                                  |  |   |                                    |
| 4: Large hood or large air mass in motion   | 4: Small hood - local control only  |                      |                        |   |   |   |   |  |                                  |  |   |                                    |
|   | <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p>   |                      |                        |   |   |   |   |  |                                  |  |   |                                    |
| <b>Individual protection measures, such as personal protective equipment</b>  |    |                      |                        |   |   |   |   |  |                                  |  |   |                                    |
| <b>Eye and face protection</b>  | <ul style="list-style-type: none"> <li>▶ "Safety glasses with side shields</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should</li> </ul>   |                      |                        |   |   |   |   |  |                                  |  |   |                                    |

|                              |   |
|------------------------------|---|
|                              | include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]"  |
| <b>Skin protection</b>       | See Hand protection below   |
| <b>Hands/feet protection</b> | <p>▶ Wear general protective gloves, eg. light weight rubber gloves.</p> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>· frequency and duration of contact,</li> <li>· chemical resistance of glove material,</li> <li>· glove thickness and</li> <li>· dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>· Contaminated gloves should be replaced.</li> </ul> <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>· Excellent when breakthrough time &gt; 480 min</li> <li>· Good when breakthrough time &gt; 20 min</li> <li>· Fair when breakthrough time &lt; 20 min</li> <li>· Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> |
| <b>Body protection</b>       | See Other protection below  |
| <b>Other protection</b>      | <p>No special equipment needed when handling small quantities.</p> <p><b>OTHERWISE:</b></p> <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ Barrier cream.</li> <li>▶ Eyewash unit.</li> </ul>  |

## Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

| Required minimum protection factor | Maximum gas/vapour concentration present in air p.p.m. (by volume) | Half-face Respirator | Full-Face Respirator |
|------------------------------------|--|----------------------|----------------------|
| up to 10                           | 1000   | A-AUS / Class1       | -                    |
| up to 50                           | 1000   | -                    | A-AUS / Class 1      |
| up to 50                           | 5000   | Airline *            | -                    |
| up to 100                          | 5000   | -                    | A-2                  |
| up to 100                          | 10000  | -                    | A-3                  |
| 100+                               |  |                      | Airline**            |

\* - Continuous Flow \*\* - Continuous-flow or positive pressure demand

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.

Continued...

- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## SECTION 9 Physical and chemical properties

### Information on basic physical and chemical properties

|   |  |  |                |
|---|--|--|----------------|
| <b>Appearance</b>                                   | Milky liquid with fragrance; mixes with water. |  |                |
| <b>Physical state</b>                               | Liquid   | <b>Relative density (Water = 1)</b>            | 1              |
| <b>Odour</b>  | Not Available                                  | <b>Partition coefficient n-octanol / water</b> | Not Available  |
| <b>Odour threshold</b>                              | Not Available                                  | <b>Auto-ignition temperature (°C)</b>          | Not Available  |
| <b>pH (as supplied)</b>                             | Not Available                                  | <b>Decomposition temperature (°C)</b>          | Not Available  |
| <b>Melting point / freezing point (°C)</b>          | Not Available                                  | <b>Viscosity (cSt)</b>                         | Not Available  |
| <b>Initial boiling point and boiling range (°C)</b> | Not Available                                  | <b>Molecular weight (g/mol)</b>                | Not Applicable |
| <b>Flash point (°C)</b>                             | Not Available                                  | <b>Taste</b>                                   | Not Available  |
| <b>Evaporation rate</b>                             | Not Available                                  | <b>Explosive properties</b>                    | Not Available  |
| <b>Flammability</b>                                 | Not Available                                  | <b>Oxidising properties</b>                    | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | Not Available                                  | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available  |
| <b>Lower Explosive Limit (%)</b>                    | Not Available                                  | <b>Volatile Component (%vol)</b>               | Not Available  |
| <b>Vapour pressure (kPa)</b>                        | Not Available                                  | <b>Gas group</b>                               | Not Available  |
| <b>Solubility in water</b>                          | Miscible                                       | <b>pH as a solution (1%)</b>                   | Not Available  |
| <b>Vapour density (Air = 1)</b>                     | Not Available                                  | <b>VOC g/L</b>                                 | Not Available  |

## SECTION 10 Stability and reactivity

|   |  |
|---|--|
| <b>Reactivity</b>                         | See section 7  |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7  |
| <b>Conditions to avoid</b>                | See section 7  |
| <b>Incompatible materials</b>             | See section 7  |
| <b>Hazardous decomposition products</b>   | See section 5  |

## SECTION 11 Toxicological information

### Information on toxicological effects

|                     |   |
|---------------------|---|
| <b>Inhaled</b>      | The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. |
| <b>Ingestion</b>    | The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.  |
| <b>Skin Contact</b> | The material is not thought to produce adverse health effects or skin irritation following contact (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable gloves be used in an occupational setting.             |
| <b>Eye</b>          | Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).  |
| <b>Chronic</b>      | Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.  |

|                         |   |                   |
|-------------------------|---|-------------------|
| 034 FOCUS OSPA ANTIFOAM | <b>TOXICITY</b>   | <b>IRRITATION</b> |
|                         | Not Available   | Not Available     |
| <b>Legend:</b>          | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances |                   |

|                                   |   |                          |   |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity                    | ✗ | Carcinogenicity          | ✗ |
| Skin Irritation/Corrosion         | ✗ | Reproductivity           | ✗ |
| Serious Eye Damage/Irritation     | ✗ | STOT - Single Exposure   | ✗ |
| Respiratory or Skin sensitisation | ✗ | STOT - Repeated Exposure | ✗ |
| Mutagenicity                      | ✗ | Aspiration Hazard        | ✗ |

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
 ✓ – Data available to make classification

## SECTION 12 Ecological information

### Toxicity

| 034 FOCUS OSPA ANTIFOAM | Endpoint   | Test Duration (hr) | Species       | Value         | Source        |
|-------------------------|--|--------------------|---------------|---------------|---------------|
|                         | Not Available  | Not Available      | Not Available | Not Available | Not Available |
| <b>Legend:</b>          | Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data |                    |               |               |               |

**DO NOT** discharge into sewer or waterways.

### Persistence and degradability

| Ingredient | Persistence: Water/Soil               | Persistence: Air                      |
|------------|---------------------------------------|---------------------------------------|
|            | No Data available for all ingredients | No Data available for all ingredients |

### Bioaccumulative potential

| Ingredient | Bioaccumulation                       |
|------------|---------------------------------------|
|            | No Data available for all ingredients |

### Mobility in soil

| Ingredient | Mobility                              |
|------------|---------------------------------------|
|            | No Data available for all ingredients |

## SECTION 13 Disposal considerations

### Waste treatment methods

|                                     |   |
|-------------------------------------|---|
| <b>Product / Packaging disposal</b> | <ul style="list-style-type: none"> <li>▶ <b>DO NOT</b> allow wash water from cleaning or process equipment to enter drains.</li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible or consult manufacturer for recycling options.</li> <li>▶ Consult State Land Waste Authority for disposal.</li> <li>▶ Bury or incinerate residue at an approved site.</li> <li>▶ Recycle containers if possible, or dispose of in an authorised landfill.</li> </ul> |
|-------------------------------------|---|

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

### Disposal Requirements

Not applicable as substance/ material is non hazardous.

## SECTION 14 Transport information

**Labels Required**

|                         |                |
|-------------------------|----------------|
| <b>Marine Pollutant</b> | NO             |
| <b>HAZCHEM</b>          | Not Applicable |

**Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code**

| Product name | Group |
|--------------|-------|
|--------------|-------|

**14.7.3. Transport in bulk in accordance with the IGC Code**

| Product name | Ship Type |
|--------------|-----------|
|--------------|-----------|

**SECTION 15 Regulatory information****Safety, health and environmental regulations / legislation specific for the substance or mixture**

This substance is to be managed using the conditions specified in an applicable Group Standard

| HSR Number     | Group Standard |
|----------------|----------------|
| Not Applicable | Not Applicable |

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

**Additional Regulatory Information**

Not Applicable

**Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Hazard Class   | Quantities     |
|----------------|----------------|
| Not Applicable | Not Applicable |

**Certified Handler**

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Class of substance | Quantities     |
|--------------------|----------------|
| Not Applicable     | Not Applicable |

Refer Group Standards for further information

**Maximum quantities of certain hazardous substances permitted on passenger service vehicles**

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

| Hazard Class   | Gas (aggregate water capacity in mL) | Liquid (L)     | Solid (kg)     | Maximum quantity per package for each classification |
|----------------|--------------------------------------|----------------|----------------|--|
| Not Applicable | Not Applicable                       | Not Applicable | Not Applicable | Not Applicable                                       |

**Tracking Requirements**

Not Applicable

**National Inventory Status**

| National Inventory                              | Status        |
|---|---------------|
| Australia - AIIC / Australia Non-Industrial Use | Not Available |
| Canada - DSL                                    | Not Available |
| Canada - NDSL                                   | Not Available |

| National Inventory            | Status  |
|-------------------------------|---|
| China - IECSC                 | Not Available   |
| Europe - EINEC / ELINCS / NLP | Not Available   |
| Japan - ENCS                  | Not Available   |
| Korea - KECI                  | Not Available   |
| New Zealand - NZIoC           | Not Available   |
| Philippines - PICCS           | Not Available   |
| USA - TSCA                    | Not Available   |
| Taiwan - TCSI                 | Not Available   |
| Mexico - INSQ                 | Not Available   |
| Vietnam - NCI                 | Not Available   |
| Russia - FBEPH                | Not Available   |
| <b>Legend:</b>                | Yes = All CAS declared ingredients are on the inventory<br>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

## SECTION 16 Other information

|                      |            |
|----------------------|------------|
| <b>Revision Date</b> | 23/08/2023 |
| <b>Initial Date</b>  | 22/04/2022 |

## SDS Version Summary

| Version | Date of Update | Sections Updated                                 |
|---------|----------------|--|
| 2.1     | 22/04/2022     | Stability and reactivity - Instability Condition |

## Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

## Definitions and abbreviations

- ▶ PC - TWA: Permissible Concentration-Time Weighted Average
- ▶ PC - STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ▶ TEEL: Temporary Emergency Exposure Limit,
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ▶ ES: Exposure Standard
- ▶ OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- ▶ LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- ▶ LOD: Limit Of Detection
- ▶ OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- ▶ PNEC: Predicted no-effect concentration
  
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- ▶ NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- ▶ NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- ▶ KECI: Korea Existing Chemicals Inventory
- ▶ NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances

- ▶ TSCA: Toxic Substances Control Act
- ▶ TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- ▶ NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.